
★ MITSUBISHI GAS CHEMICAL CO., INC.

TETRAD-X

N,N,N',N'-tetraglycidyl-mxylenediamine CAS: 63738-22-7 EINECS: 264-438-6



Product Information

Description	N,N,N',N' -tetraglycidyl-m-xylenediamine ($C_{20}H_{28}N_2O_4$)	
Features	Low viscosityExcellent mechanical propertiesPoly functional liquid epoxy resin	
Physical Properties	Appearance, (Visual)	Pale yellow liquid
	Molecular weight	360.5
	Flash point, °C, (Cleveland open tester) $_$	242
	Specific gravity, d ²⁵ ₄	1.14 - 1.16
	Amine value, mgKOH/g	
	Solubility Soluble in benzene, toluene, xylene,	
	methanol, diethyl ether, acetone, methyl ethyl ketone,	
	ethyl acetate, <i>n</i> -butanol, <i>i</i> -propanol, dimethylformamide	
Specification	Color, (Gardner)	≦5
	Viscosity, mPa·s, 25°C	
	Volatile matter, %	
	Epoxy equivalent weight	
Container Information	Available in 180 kg steel drums.	
Safety & Handling	Avoid breathing vapor and direct contact with skin, eyes and clothing. Always refer to the MSDS for detailed safety information.	
Contact Information	Fmail: mxda@mgc.co.in Website	www mgc co in

The information presented herein is believed to be accurate and reliable, but is presented without guarantee of responsibility on the part of Mitsubishi Gas Chemical Company. It is the responsibility of the users to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patents.